

2018 USPKS Rule Book Updates

New Rule:

201.18.2 Push Back Nose Cone Mount:

The push back nose cone mount shall be mounted as pictured below with the arrow pointing upward.



Update/Clarification on Rule:

502.21 Yamaha KT100 Spec:

Minimum Intake Track Length	2.60"
Maximum Intake Track Length	2.70"
Combustion Chamber CC, W/LAD Plug	11
Minimum Exhaust Port Height	1.155"
Maximum Intake Port Opening	0.775"
Minimum Blow Down	0.390"
Minimum Exhaust Rib Width	0.140"
Maximum Exhaust Chord Width	1.551"
Maximum Intake Chord Width	1.370"
Maximum Small Transfer Port Chord Width	0.485"
Maximum Large Transfer Port Chord Width	0.995"
Maximum Small Transfer Port Height (bottom to top)	0.475"
Update change from 0.475" to 0.530"	0.530"
Maximum Large Transfer Port Height (bottom to top)	0.530"
Update change from 0.530" to 0.475"	0.475"
Maximum Cylinder Bore	2.090"
Maximum Piston Stroke	1.816"
Maximum Piston Skirt Chamfer	0.030"
Minimum Wrist Pin Length	1.565"
Maximum Wrist Pin ID	0.410"
Minimum Wrist Pin OD	0.550"
Maximum Wrist Pin OD	0.552"
Minimum Outside Crank Width	1.790"
Minimum Inside Crank Width	0.343"
Maximum Pulse Hole ID (No-Go)	0.128"